

Telephone:
 Fax:
 VAT Registration No.:

Dimensions				
Notes			Specified value	Measured value
	Wheelbase	mm	2450	
	Track - front/rear	mm	1420/1380	
Tightening torques				
Notes			Specified value	Measured value
2	Tightening torque - steel wheels		110 Nm	
	Trackrod locknut/clamp		60 Nm	
Checking range - Front wheels				
Notes			Specified value	Measured value
	Load positioning		Unladen	
	Fuel tank - percentage full	%	100	
	Toe-in (N = negative, toe-out)	mm	0 - 2	
	Toe-in	deg	0° - 0°20'	
	Toe-in	deg-1/100	0 - 0,33	
	Camber	deg	0° - 1°N	
	Camber	deg-1/100	0 - 1N	
	Castor	deg	0°35' - 2°5'	
	Castor	deg-1/100	0,58 - 2,08	
Setting data - All wheels				
Notes			Specified value	Measured value
	Load positioning		Unladen	
	Fuel tank - percentage full	%	100	
	Toe-in (N = negative, toe-out)	mm	1±1	
	Toe-in	deg	0°10'±10'	
	Toe-in	deg-1/100	0,17±0,17	
	Camber	deg	0°30'N±30'	
	Camber	deg-1/100	0,50N±0,50	
	Camber adjustment		Not adjustable	
	Castor	deg	1°20'±45'	
	Castor	deg-1/100	1,33±0,75	
	Castor adjustment		Not adjustable	
	KPI (SAI)	deg	12°15'±50'	
	KPI (SAI)	deg-1/100	12,25±0,83	
	Included angle	deg	11°45'	
	Included angle	deg-1/100	11,75	
	Rear toe-in	mm	1,60±1,40	
	Rear toe-in	deg	0°16'±14'	
	Rear toe-in	deg-1/100	0,27±0,23	
	Rear toe-in adjustment		Not adjustable	
	Rear camber	deg	1°24'N±30'	
	Rear camber	deg-1/100	1,40N±0,50	
	Rear camber adjustment		Not adjustable	

Autodata Note 2

- Do NOT lubricate bolts or mating surfaces.