



# STBV32

## HIGH VOLTAGE FAST-SWITCHING NPN POWER TRANSISTOR

- n HIGH VOLTAGE CAPABILITY
- n LOW SPREAD OF DYNAMIC PARAMETERS
- n MINIMUM LOT-TO-LOT SPREAD FOR RELIABLE OPERATION
- n VERY HIGH SWITCHING SPEED

### APPLICATIONS


- n COMPACT FLUORESCENT LAMPS (CFLS)

### DESCRIPTION


The device is manufactured using High Voltage Multi Epitaxial Planar technology for high switching speeds and high voltage capability. It uses a Cellular Emitter structure with planar edge termination to enhance switching speeds while maintaining the wide RBSOA.

The STBV series is designed for use in Compact Fluorescent Lamps.

**Figure 1: Package**



**Figure 2: Internal Schematic Diagram**



**Table 1: Order Codes**

Part Number	Marking	Package	Packaging
STBV32	BV32	TO-92	Bulk
STBV32-AP	BV32	TO-92	Ammopack

**Table 2: Absolute Maximum Ratings**

Symbol	Parameter	Value	Unit
$V_{CES}$	Collector-Emitter Voltage ( $V_{BE} = 0$ )	700	V
$V_{CEO}$	Collector-Emitter Voltage ( $I_B = 0$ )	400	V
$V_{EBO}$	Emitter-Base Voltage ( $I_C = 0$ , $I_B = 0.5$ A, $t_p < 10$ ms)	$V_{(BR)EBO}$	V
$I_C$	Collector Current ( $f \geq 100$ Hz, duty-cycle $\leq 50$ %, $T_C = 25$ °C)	1.5	A
$I_{CM}$	Collector Peak Current ( $t_p < 5$ ms)	3	A
$I_B$	Base Current	0.5	A
$I_{BM}$	Base Peak Current ( $t_p < 5$ ms)	1.5	A
$P_{tot}$	Total Dissipation at $T_C = 25$ °C	1.5	W

Symbol	Parameter	Value	Unit
$T_{stg}$	Storage Temperature	-65 to 150	°C
$T_J$	Max. Operating Junction Temperature	150	°C

**Table 3: Thermal Data**

$R_{thj-case}$	Thermal Resistance Junction-case	Max	83.3	°C/W
$R_{thj-amb}$	Thermal Resistance Junction-Ambient	Max	112	°C/W

**Table 4: Electrical Characteristics ( $T_{case} = 25\text{ °C}$  unless otherwise specified)**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$I_{CEV}$	Collector Cut-off Current ( $V_{BE} = -1.5\text{ V}$ )	$V_{CE} = 700\text{ V}$ $V_{CE} = 700\text{ V}$ $T_J = 125\text{ °C}$			1 5	mA mA
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage ( $I_C = 0$ )	$I_E = 10\text{ mA}$	9		18	V
$V_{CEO(sus)}^*$	Collector-Emitter Sustaining Voltage ( $I_B = 0$ )	$I_C = 10\text{ mA}$	400			V
$V_{CE(sat)}^*$	Collector-Emitter Saturation Voltage	$I_C = 0.5\text{ A}$ $I_B = 100\text{ mA}$ $I_C = 1\text{ A}$ $I_B = 250\text{ mA}$ $I_C = 1.5\text{ A}$ $I_B = 500\text{ mA}$			0.5 1 1.5	V V V
$V_{BE(sat)}^*$	Base-Emitter Saturation Voltage	$I_C = 0.5\text{ A}$ $I_B = 100\text{ mA}$ $I_C = 1\text{ A}$ $I_B = 250\text{ mA}$			1.0 1.2	V V
$h_{FE}$	DC Current Gain	$I_C = 0.5\text{ A}$ $V_{CE} = 2\text{ V}$ $I_C = 1\text{ A}$ $V_{CE} = 2\text{ V}$	8 5		35 25	
$t_r$ $t_s$ $t_f$	RESISTIVE LOAD Rise Time Storage Time Fall Time	$I_C = 1\text{ A}$ $V_{CC} = 125\text{ V}$ $I_{B1} = -I_{B2} = 200\text{ mA}$ $t_p = 25\text{ }\mu\text{s}$ (see figure 12)			1 4 0.7	$\mu\text{s}$ $\mu\text{s}$ $\mu\text{s}$
$t_s$	INDUCTIVE LOAD Storage Time	$I_C = 1\text{ A}$ $V_{clamp} = 300\text{ V}$ $I_{B1} = 200\text{ mA}$ $V_{BE(off)} = -5\text{ V}$ $L = 50\text{ mH}$ $R_{BB} = 0$ (see figure 13)		0.8		$\mu\text{s}$

\* Pulsed: Pulsed duration = 300  $\mu\text{s}$ , duty cycle  $\leq 1.5\%$ .

Figure 3: Safe Operating Area




Figure 4: Output Characteristics




Figure 5: Base-Emitter Saturation Voltage




Figure 6: Derating Curve




Figure 7: Collector-Emitter Saturation Voltage




Figure 8: DC Current Gain




Figure 9: DC Current Gain




Figure 10: Reverse Biased Operating Area








Figure 11: Inductive Load Switching Times



**Figure 12: Resistive Load Switching Test Circuit****Table 13: Inductive Load Switching Test Circuit**


## TO-92 BULK SHIPMENT MECHANICAL DATA

DIM.	mm.		
	MIN.	TYP	MAX.
A	4.32		4.95
b	0.36		0.51
D	4.45		4.95
E	3.30		3.94
e	2.41		2.67
e1	1.14		1.40
L	12.70		15.49
R	2.16		2.41
S1	0.92		1.52
W	0.41		0.56
V		5 °	



**TO-92 AMMOPACK SHIPMENT (Suffix"-AP") MECHANICAL DATA**

DIM.	mm.		
	MIN.	TYP	MAX.
A1			4.80
T			3.80
T1			1.60
T2			2.30
d			0.48
P0	12.50	12.70	12.90
P2	5.65	6.35	7.05
F1,F2	2.44	2.54	2.94
delta H	-2.00		2.00
W	17.50	18.00	19.00
W0	5.70	6.00	6.30
W1	8.50	9.00	9.25
W2			0.50
H	18.50		20.50
H0	15.50	16.00	16.50
H1			25.00
D0	3.80	4.00	4.20
t			0.90
L			11.00
I1	3.00		
delta P	-1.00		1.00



## STBV32

---

**Figure 1: Revision History**

Version	Release Date	Change Designator
01-Dec-2002	1	First Release.
27-Apr-2005	1	Total dissipation value has been modified.



Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

All other names are the property of their respective owners

© 2005 STMicroelectronics - All Rights Reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan -  
Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America  
**[www.st.com](http://www.st.com)**